PL protecting covers
Screw clamp terminal block accessories

PL

Mounting instructions



– The mounting of the PL does not require a screwdriver,
– The dismounting of the PL requires a screwdriver DIA .4 mm *0.160 in*, the screwdriver must be positionned in the cover centered hole.

Description

– Prohibit access to the screw clamps,
– Indicate live circuits.

Ordering details

Description	Color	Type	Order code		Pkg qty	Weight (1 pce) g
5.2 mm *0.205 in* spacing	Transparent ☒	PL5	1SNK900618R0000		10	1.50
6 mm *0.236 in* spacing		PL6	1SNK900619R0000		10	1.80
8 mm *0.315 in* spacing		PL8	1SNK900620R0000		10	2.60
10 mm *0.394 in* spacing		PL10	1SNK900621R0000		10	3.10
16 mm *0.630 in* spacing		PL16	1SNK900622R0000		10	4.60

Main technical data

Material specifications	Insulating material	Polycarbonate	
	Flammability	V2	
	NF F 16 101		
Ambient temperature min/max	Service IEC 60068-2-1	-55 ... +110 °C	*-67 ... +230 °F*
	Storage	-55 ... +110 °C	*-67 ... +230 °F*
	Installing	-5 ... +40 °C	*+23 ... +104 °F*

All the main technical data provided are "manufacturer" values

RoHS
RoHS

Mounting instructions

Tool	⊘	Flat screwdriver Ø 4 mm *Ø 0.157 in*

5

1SNK160021S0201

All the technical data for UL/CSA standard and dimensions in inches are in italic.
Technical data valid for copper conductors only.