Automation Systems Interconnect, Inc.
Innovative Interconnect and Interface Solutions

Industrial Form C – 9.4mm
Molded Cable Assemblies
For Solenoid Valve Applications



DUAL JUMPED GROUND PINS – Molded cable assemblies can be mounted with cable exiting the ground side or opposite.

* Four wire units have one ground pin and 3 “U” shaped pins. Cable exit direction must be specified.

Molded Cable Assemblies
Black PVC Cable & Connector



3 Pole (3 Flat Pins)

Part Numbers	Cable Length	Poles	
0 to 250 VAC/DC  Without LED & Suppression	3 Meter (9.8 Feet)	3	CP2-N02-000-C01-3
	5 Meter (16.4 Feet)	3	CP2-N02-000-C01-5
	3 Meter (9.8 Feet)	4*	
	5 Meter (16.4 Feet)	4*	
12 to 24 VAC/DC  With LED & Suppression	3 Meter (9.8 Feet)	3	CP2-N02-VL1-C01-3
	5 Meter (16.4 Feet)	3	CP2-N02-VL1-C01-5
110 to 120 VAC/DC  With LED & Suppression	3 Meter (9.8 Feet)	3	CP2-N02-VL2-C01-3
	5 Meter (16.4 Feet)	3	CP2-N02-VL2-C01-5

Technical Information

Connection Voltage	As Listed in Drawing	Cable Type	HO3VVF
Nominal Power	3A	Jacket Material	Black PVC
Test Voltage	250VAC - 300 VDC max.	Conductor Size	20/3 AWG
Insulation Group	VDC 0110 1/89 Class C	Conductor Color	Brn, Blue, (Blk), Grn/Yel
Clamping Voltage 24V	42V	Nominal Cable OD	6.7mm
Clamping Voltage 110V	185V	Bend Radius	10 X Cable OD
Connector Material	Glass Reinforced Polypropylene	Center Screw	M3 x 21.5mm
Protection Rating	IP 65; IP 67 on Request	Temperature Range	-2° to +176° F
Contact Resistance	$\leq$ 4 mΩ		