NEMA configurations for select devices

Poles, wires	Rating	NEMA prefix	15A Straight blade		20A Straight blade	
			Receptacle, connector & flanged outlet	Plug & flanged inlet	Receptacle, connector & flanged outlet	Plug & flanged inlet
2-pole, 2-wire	125V/AC	1	4882 ◇ 1-15R	4862 ◆ 1-15P		
2-pole, 3-wire grounding	125V/AC	5	AH5262C □MC AH5252 □ 6262 □D AHIG5262 □IM AH5269 ◇U 5261 △M 1547 ◇Y VGF15 □GM TRBR15 □R TRVGF15 □RGM 5262 □M AH8200 □M 8200 □HM 8210 △M IG8200 □IM TR8200 □RM VGFH15 □GM TRVGFH15 □RGM 5269N ◇NC 5279C ○ AH5969 ◇O WRVGF15 □ 60W47 △Y 60W47DPLX □W 15W47 ◇W 4887 ◇ BR15 □ CR15 □ IG5262 ◇O 5269NHG ◇N AH8219HG ◇U AH8119W ◇O 5-15R	5266N ◆NC 5278C ● AH5266 ◆U AH5965 ◆O 1447 ◆Y 14W47 ◆W 4867 ◆ 5266NHG ◆N AH8215HG ◆U AH8115W ◆O 5-15P	AH5362 □MC AH5352 □M 6362 □DM AHIG5362 □IM 1533 ◇Y 15W33 ◇W 5361 △M VGF20 □GM TRBR20 □R TRVGF20 □RGM 5362 □M AH8300 □M 8300 □M 8310 △M IG8300 □IM TR8300 □RM VGFH20 □GM TRVGFH20 □RGM 5369N ◇NC 5779C ○ AH5369 ◇U WRVGF20 □ 60W33 △W 60W33DPLX □W AH5369Y ◇O 4228 ◇ BR20 □ CR20 □ IG5362 ◇O 5369NHG ◇N AH8319HG ◇U 5-20R	5366N ◆NC 5778C ● AH5366 ◆U AH5364Y ◆O 1433 ◆Y 14W33 ◆W 4409 ◆ 5366NHG ◆N AH8315HG ◆U 5-20P
	250V/AC	6	AH5662 □M 5661 △ AHIG5662 □I 6662 □D 1549 ◇Y 15W49 ◇W 826 □ 816 △ 5662C □ AH8600 □M 5669N ◇N 5679C ○ AH5669 ◇U 60W49 △W 60W49DPLX □W AH5669Y ◇O 4227 ◇ 8610 △ 6-15R	5666N ◆N 5678C ● AH5666Y ◆O AH5666 ◆U 1449 ◆Y 14W49 ◆W 4866 ◆ AH8225HG ◆U 6-15P	AH5462 □M 5461 △ AHIG5462 □I 6462 □D 1548 ◇Y 15W48 ◇W 815 □ 5462C □ AH8400 □M IG8400 □I 5469N ◇N 5879C ○ AH5469 ◇L 60W48 △W 60W48DPLX □W AH5469Y ◇O 4229 ◇ 8410 △ 6-20R	5466N ◆N AH5464Y ◆O 5878C ● AH5466 ◆U 1448 ◆Y 14W48 ◆W 4509 ◆ AH8325HGA ◆AU 6-20P
	277V/AC	7	5302 □ 7-15R	7-15P	7-20R	7624N ◆L 7-20P
3-pole, 3-wire	125/250V/AC	10			805 △ 10-20R	9151N ◆L 2836 ◆ 10-20P
3-pole, 4-wire grounding	125/250V/AC	14			5759 △ 14-20R	14-20P
	3Ø 250V/AC	15				
4-pole, 4-wire	3ØY 120/208V/AC	18				7251N ◆L 18-20P

Straight blade legend: How to use the chart

Core catalog number color indicates a device's grade:

BLACK = Industrial specification grade
BLUE = Commercial specification grade
ORANGE = Construction specification grade
GREEN = Hospital specification grade

A suffix combining a **RED** shape and alpha letter indicate a device's body, type and available options.

Device body:

- □ Duplex receptacle
- △ Single receptacle
- ◆ Plug
- ◇ Connector
- ● Flanged inlet
- ○ Flanged outlet
- ◗ Hull inlet
- ➢ Mechanical interlock

Open shape has holes (receptacles, connectors, outlets)
Closed shape has blades (plugs, inlets)

Device type:

- **A** Angled
- **D** Decorator
- **G** GFCI
- **H** Compact
- **I** Isolated ground
- **L** Safety grip
- **N** Auto grip
- **O** Quick grip
- **R** Tamper resistant
- **S** Surface
- **U** Ultra grip

Device options available:

- **C** Corrosion resistant
- **M** ArrowLink modular
- **W** Watertight
- **Y** Severe duty insulated

Due to spatial constraints not all products are shown on this page. For additional product options in these configurations consult sections A, B, I, J & K.