




1) Mode settings, 2) Optical axis receiver, 3) Optical axis emitter, 4) Power indicator, 5) stability, 6) Sn



Basic features

Approval/Conformity	cULus
	CE
	UKCA
	WEEE
Principle of operation	Photoelectric sensor
Series	R090K
Style	Square
	Connection 90°

Display/Operation

Adjuster	6-turn potentiometer
	Rotary switch 2 positions
Display	Output function- LED yellow
	Stability - LED green
Setting	Rated switching distance (Sn)
	Light-on/dark-on

Electrical connection

Connection	Connector, M8x1, 4-pin
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

No-load current I_0 max. at U_e	20 mA
Operating voltage U_b	10...30 VDC
Rated operating current I_e	100 mA
Rated operating voltage U_e DC	24 V
Ready delay t_v max.	300 ms
Ripple max. (% of U_e)	10 %
Switching frequency	1000 Hz
Turn-off delay t_{off} max.	0.5 ms
Turn-on delay t_{on} max.	0.5 ms
Voltage drop U_d max. at I_e	2 V

Environmental conditions

Ambient temperature	-35...55 °C
IP rating	IP67

Photoelectric Sensors
BOS R090K-PU-RH10-S75
Order Code: BOS029M

BALLUFF

Functional safety

MTTF (40 °C) 92 a

Interface

Switching output PNP normally open/normally closed (NO/NC)

Material

Housing material PC
PBT
Material sensing surface PMMA

Mechanical data

Dimension 10.7 x 43.5 x 19.5 mm
Mounting part Screw M3
Tightening torque max. 0.5 Nm

Optical features

Ambient light max. 10000 Lux
Beam characteristic Focus, typical at 90 mm
Light spot size Ø 4.5 mm at 60 mm
Light type LED, red light
Principle of optical operation Diffuse sensor, triangulation
Special optical feature Background suppression
Switching function, optical dark-on/light-on
Wave length 660 nm


Range/Distance

Range 20...350 mm
Rated operating distance Sn 350 mm Adjustable

Connector Drawings



Wiring Diagrams



Opto Symbols

