DRAWING NO. SE208001

REV	DATE	DESCRIPTION	ECO	BY	C'H'K.
L	01/27/2016 16:12:00 PM	NOTE 13 UPDATED --	42724	TS	NJ

CATALOG NO.	CONDUCTOR			BOLT SIZE	FIG. NO.	DIMENSIONS									BURNDY® INSTALLATION TOOLING (# CRIMPS)								
	FLEX	CODE (AWG)	NAVY 5			B	C	H	K	L	N	O.D.	T REF.	Z MIN.	DIE INDEX	COLOR CODE	MECHANICAL RATCHET MD7-34R MD6	MECHANICAL RATCHET OUR840	HYDRAULIC BCT500 Y500CT PAT600	HYDRAULIC Y750, Y35 Y39, PAT750	HYDRAULIC Y46 PAT46 4	HYDRAULIC Y45 3	DIELESS (# CRIMPS)	WIRE STRIP LENGTH
YAV28LTCI4FX	4/0 AWG CLASS G-M DLO (550/24) 120 mm² CLASS 2,5	4/0 AWG CLASS B,C	200	1/4	1	1.03 [26]	1.14 [29]	-----	.27 [7]	2.23 [57]	.31 [8]	.77 [20]	.15 [4]	.33 [8]	15	PURPLE	W28RT (2) X28RT (3) W28VT (2)	X28RT (3) W28VT (2)	W28RT (2) X28RT (3) W28VT (2)	U28RT UR4205WE (1)	U28RT UR4205WE (1)	U28RT UR4205WE (1)	MECHANICAL: MY29-11 (1) HYDRAULIC: Y644M (1) PAT644 (1) Y81KFT (2) PAT81KFT (2) Y4PC834 (2) PAT4PC834 (2)	1-1/16"
YAV28LTCI4FX45					2			1.70 [43]		2.11 [53]														
YAV28LTCI4FX90					3			1.83 [47]		1.14 [29]														
YAV28LNT5I6FX				5/16	1		.94 [24]	-----	.33 [8]	2.29 [58]	.34 [9]			.36 [9]										
YAV28LNT5I6FX45					2			1.70 [43]		2.17 [55]														
YAV28LNT5I6FX90					3			1.83 [47]		1.21 [31]														
YAV28LTC5I6FX				5/16	1		1.14 [29]	-----	.33 [8]	2.29 [58]	.34 [9]			.36 [9]										
YAV28LTC5I6FX45					2			1.70 [43]		2.17 [55]														
YAV28LTC5I6FX90					3			1.83 [47]		1.21 [31]														
YAV28LNT38FX				3/8	1		.94 [24]	-----	.41 [10]	2.42 [61]	.41 [10]			.42 [11]										
YAV28LNT38FX45					2			1.70 [43]		2.29 [58]														
YAV28LNT38FX90					3			1.83 [47]		1.33 [34]														
YAV28LTC38FX				3/8	1		1.14 [29]	-----	.41 [10]	2.42 [61]	.41 [10]			.42 [11]										
YAV28LTC38FX45					2			1.70 [43]		2.29 [58]														
YAV28LTC38FX90					3			1.83 [47]		1.33 [34]														
YAV28LTCI2FX				1/2	1			-----	.53 [13]	2.67 [68]	.53 [13]			.55 [14]										
YAV28LTCI2FX45					2			1.70 [43]		2.54 [65]														
YAV28LTCI2FX90					3			1.83 [47]		1.58 [40]														
YAV28LTC58FX				5/8	1			-----	.69 [17]	2.92 [74]	.66 [17]			.67 [17]										
YAV28LTC58FX45					2			1.70 [43]		2.79 [71]														
YAV28LTC58FX90					3			1.83 [47]		1.83 [46]														
YAV28LTC34FX	4/0 AWG CLASS G-M DLO (550/24) 120 mm² CLASS 2,5	4/0 AWG CLASS B,C	200	3/4	1	1.03 [26]	1.14 [29]	-----	.81 [21]	3.11 [79]	.75 [19]	.77 [20]	.15 [4]	.77 [19]	15	PURPLE	W28RT (2) X28RT (3) W28VT (2)	X28RT (3) W28VT (2)	W28RT (2) X28RT (3) W28VT (2)	U28RT UR4205WE (1)	U28RT UR4205WE (1)	U28RT UR4205WE (1)		1-1/16"
YAV28LTC34FX45					2			1.70 [43]		2.98 [76]														
YAV28LTC34FX90					3			1.83 [47]		2.02 [51]														

SEE SHEET 1 OF 18 FOR NOTES

TO ORDER BURNDY® PRO

HYLUG™

ITEM NO:	N/A	
CAT. NO:	YAV28L- (TABLE)	
DRAWN BY:	D FILLION	11/30/92
CHECKER:	K HENRY	12/02/92
DSN APPVL:	C PALAGI	12/04/92
MFG APPVL:	--	--
QA APPVL:	A LLOYD	12/02/92
MKT APPVL:	T NELSON	12/04/92
PROD FAM:	CM&R Compression	
PROJECT #:	--	
DOCUMENT TYPE:	Sales	
REL LEVEL:	Released	

SCALE: 1:1

SIZE	DRAWING NO	REV
D	SE208001	L
	SHEET 10 OF 18	

REV: PE0200