Triple-deck terminal blocks + ground protection

Compression clamp

DIN 3

D 4/6.P.T1

Spacing 6 mm *(.238")*



Ground terminal block to be used with D4/6.T...

Color	Type	Part numbers
7 clamps electrically grounded to the mounting rail		
Green/yellow V0	**D 4/6.P.T1**	**0199 220.00**

End stop	th. 12 mm	**BADH** V2		**0116 900.27**
End stop	th. 9,1 mm	**BAMH** V0		**0194 836.01**
End stop	th. 9,1 mm	**BAMH** V2		**0114 836.00**
Other end stops : see Accessories section				
Rail	35 x 7,5 x 1	**PR3G2**		**0164 800.03**
Rail	35 x 7,5 x 1	**PR3Z2**		**0174 300.17**
Rail	35 x 7,5 x 1	**PR30**	prepunched	**0173 220.05**
Rail	35 x 15 x 2,3	**PR4**		**0168 500.12**
Rail	35 x 15 x 1,5	**PR5**	prepunched	**0101 598.26**
Other rails : see Accessories section				
Other accessories : see Accessories section				

Characteristics

Wire size

		IEC NFC DIN	UL	CSA
Compression clamp	Solid wire	0,2-4 mm²	24-10 AWG	24-10 AWG
	Stranded wire	0,22-4 mm²	24-10 AWG	24-10 AWG

Voltage

Rated			
Pulse			
Pollution degree			

Current

Rated / Short circuit	480 A/1s		

Wire size

Rated/gauge	4 mm² / A4	10 AWG	10 AWG

Wire stripping length	Recommended screwdriver	Recommended torque	Protection
9,5 mm *.37 "*	4 mm *.16"*	0,5-0,8 Nm *4.4-7 lb.in*	IP 20 *NEMA 1*

Notes

In this block, all circuits are connected to the mounting rail.

Accessories

2

3

		Type		Part numbers
1	End section	No end section needed : closed block		
2	Comb type jumper bar	**PC61**	10 poles	**0163 311.22**
3	IDC jumper 24A	**AD2,5**	V2	**0114 205.20**

R

R See section on markers marking method ⑤ RC65 blank (white, red, blue)