Selection Tables

Listed below are our standard voltages. Other primary and secondary voltages available are 240, 380 and 600.

COPPER WOUND, THREE PHASE

460 Delta Primary Volts 400Y Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 246 - 253)	Dimensions Width	Depth	Height	Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 259 - 271)
7.5	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
11	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
14	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
20	**DE020JHCN**	NH6	23.90	25.00	28.75	270	F or W *	SCD 7
27	**DE027JHCN**	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
34	**DE034JHC**	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
40	**DE040JHC**	NH6	23.90	25.00	28.75	380	F or W *	SCD 7
51	**DE051JHC**	NH6	23.90	25.00	28.75	450	F or W *	SCD 7
63	**DE063JHC**	NH3	26.00	25.00	38.00	550	F or W *	SCD 7
75	**DE075JHC**	NH3	26.00	25.00	38.00	600	F or W *	SCD 7
93	**DE093JHC**	NH3	26.00	25.00	38.00	630	F or W *	SCD 7
118	**DE118JHC**	NH3	26.00	25.00	38.00	880	F	SCD 7
145	**DE145JHC**	NH4	32.00	29.50	41.00	930	F	SCD 7
175	**DE175JHC**	NH4	32.00	29.50	41.00	1100	F	SCD 7
220	**DE220JHC**	NH4	32.00	29.50	41.00	1450	F	SCD 9
275	**DE275JHC**	NJ1	39.50	34.00	51.50	1680	F	SCD 9
330	**DE330JHC**	NJ1	39.50	34.00	51.50	1850	F	SCD 9
440	**DE440JHC**	NJ2	48.50	38.40	59.00	2350	F	SCD 10
550	**DE550JHC**	NJ2	48.50	38.40	59.00	2800	F	SCD 10
660	**DE660JHC**	NJ3	51.50	43.40	66.00	3250	F	SCD 10

For shielded units, please replace the suffix "C" with a 'K' on the above part numbers. (i.e. DE075JHK)

Refer to pages 254 to 256 for details.

460 Delta Primary Volts 460Y Secondary Volts 60 Hz

kVA	Catalog Number	Case Style (Pages 246 - 253)	Dimensions Width	Depth	Height	Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 259 - 271)
7.5	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
11	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
14	Outside of C802.2/TP1 guidelines, refer to Non-Energy Efficient Drive Isolation Transformers on page 129							
20	**DE020JJCN**	NH6	23.90	25.00	28.75	270	F or W *	SCD 7
27	**DE027JJCN**	NH6	23.90	25.00	28.75	330	F or W *	SCD 7
34	**DE034JJC**	NH6	23.90	25.00	28.75	350	F or W *	SCD 7
40	**DE040JJC**	NH6	23.90	25.00	28.75	380	F or W *	SCD 7
51	**DE051JJC**	NH6	23.90	25.00	28.75	450	F or W *	SCD 7
63	**DE063JJC**	NH3	26.00	25.00	38.00	550	F or W *	SCD 7
75	**DE075JJC**	NH3	26.00	25.00	38.00	600	F or W *	SCD 7
93	**DE093JJC**	NH3	26.00	25.00	38.00	630	F or W *	SCD 7
118	**DE118JJC**	NH3	26.00	25.00	38.00	880	F	SCD 7
145	**DE145JJC**	NH4	32.00	29.50	41.00	930	F	SCD 7
175	**DE175JJC**	NH4	32.00	29.50	41.00	1100	F	SCD 7
220	**DE220JJC**	NH4	32.00	29.50	41.00	1450	F	SCD 9
275	**DE275JJC**	NJ1	39.50	34.00	51.50	1680	F	SCD 9
330	**DE330JJC**	NJ1	39.50	34.00	51.50	1850	F	SCD 9
440	**DE440JJC**	NJ2	48.50	38.40	59.00	2350	F	SCD 10
550	**DE550JJC**	NJ2	48.50	38.40	59.00	2800	F	SCD 10
660	**DE660JJC**	NJ3	51.50	43.40	66.00	3250	F	SCD 10

For shielded units, please replace the suffix "C" with a 'K' on the above part numbers. (i.e. DE075JJK)

*Wall mounting kit and/or drip plate kit required. for details.

Products listed on this page are available as 'CE Mark' products. Please consult our sales office.