Paint Mask Labels

Paint Masks - Polyester Film

HellermannTyton thermal transfer self-laminating Paint Mask Labels are conformable with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels utilize an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.

Features and Benefits

- Paint Mask Labels provide permanent paint protection but can still be removed at any time when required.
- Paint Mask Labels withstand chemicals and heat to survive the painting process.

MATERIAL	Polyester Film
Adhesive	Acrylic
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
Min. Application Temp.	+50°F (+10 °C)

RoHS

PART NO.	TYPE	Label Width (W) in. (mm)	Height of Printable Area (H) in. (mm)	Label Height (H2) in. (mm)	Min. Bundle Diameter in. (mm)	Max. Bundle Diameter in. (mm)	Liner Width in. (mm)	Qty. per Roll
596-96255	**PW.25W1P**	1.00 (25.4)	0.75 (19.1)	4.75 (120.6)	0.13 (3.2)	0.38 (9.5)	2.00 (50.8)	1000
596-96263	**PW2.75W1P**	1.00 (25.4)	1.50 (38.1)	4.37 (110.9)	0.63 (15.8)	0.88 (22.2)	2.38 (60.4)	500
596-96261	**PW.50W1P**	1.00 (25.4)	1.50 (38.1)	7.43 (188.7)	0.38 (9.5)	0.63 (15.8)	3.00 (76.2)	500
596-96258	**PW2.75W2P**	2.00 (50.8)	1.50 (38.1)	4.37 (110.9)	0.63 (15.8)	0.88 (22.2)	4.20 (106.6)	500
596-96256	**PW.50W2P**	2.00 (50.8)	1.50 (38.1)	7.43 (188.7)	0.38 (9.5)	0.63 (15.8)	3.00 (76.2)	500

Dimensions are approximate and subject to technical changes. Use Part No. for ordering and Type for specification purposes.

MIL

Please note! Not all products listed on this page may have this approval. Please check our website for latest approvals.