ELECTRICAL DATA: No. of Cont.	CABLE AWG	CABLE Type	Max. Cable Rating Amp	Max. Cable Rating Volts	DESCRIPTION: Polarized by	DESCRIPTION: Type of Seal	DIMENSIONS (Approx. Inches) A	B	C	D	E	Assy. Lgth.	PLUG PART NUMBERS Without Safety Chain: Male	Female	With Safety Chain: Male	Female	RECEPTACLE PART NUMBERS With Covers: Male	Female	Assy. Lgth.	DIMENSIONS (Approx. Inches) A	B	C	D	E	F	G	H	PART NUMBER: Wiring Box	DIMENSIONS (Approx. Inches) I	J	K	L	M	N	Inp Co Op
FOUR POLE																																				
4	14	SO	12	600	Pin Arrange-ment	Short Female Shroud	1	1 1/4	2 3/4	3 11/16	4 7/16	16" 10'	X8059-11	X8059-15	X8059-56 X8059-114	X8059-51 X8059-116	X8059-25	X8059-26	Term. Back	1	2 3/4	1 5/8	4	4 5/8	9/32	2 7/8	5/8	SBM4140	3 1/8	2 3/4	2 3/8	5	4 1/4	5/16	3/4
4	14	SO	12	600	Pin Size	Full Male Shroud	1 5/8	1 5/8	3 1/4	5 3/8	3 5/16	30"	X8064-4	X8064-1	X8064-5	X8064-2																				
4	10	SO	20	600	Pin Size	Short Male Shroud	1 1/8	1 5/8	3 3/4	5	5 1/2	24" 10'	X8060-15	X8060-2	X8060-22 X8060-197	X8060-26 X8060-199	X8060-31	X8060-33	Term. Back	1 1/8	3 3/4	2	5 1/4	6	9/32	3 5/16	13/16	SBM4144	3 1/2	3	2 3/4	6 3/8	5 3/8	3/8	1
4	10	SO	20	600	Ground Pin Rev.	Short Male Shroud	1 1/8	1 5/8	3 3/4	4 13/16	5 3/4	30"	X8401-6	X8401-5																						
4	8	W	30	600	Pin Size	Short Female Shroud	1 1/8	1 5/8	3 3/4	4 9/16	6	24" 10'	X8061-2	X8061-3	X8061-17 X8061-120	X8061-20 X8061-122	X8061-39	X8061-10	Term. Back	1 1/4	3 7/8	2	5 1/4	6	9/32	3 5/16	13/16	SBM4144	3 1/2	3	2 3/4	6 3/8	5 3/8	3/8	1
4	8	W	30	600	Pin Size	Full Male Shroud	1 5/8	1 7/8	4 1/16	6 1/2	5 9/16	30"	X8065-1	X8065-2																						
4	8	W	30	600	Ground Pin Rev.	Short Male Shroud	1 1/8	1 5/8	3 3/4	5 3/8	5 1/8	30"	X8364-6	X8364-3	X8364-8	X8364-5																				
4	6	W	40	600	Pin Size	Short Male Shroud	1 1/4	1 5/8	4 1/4	5 3/8	6 1/2	30" 6' 10'	X8062-8 X8062-116 X8062-117	X8062-24 X8062-118 X8062-119	X8062-6 X8062-113 X8062-120	X8062-18 X8062-121 X8062-122	X8062-33	X8062-27	Term. Back	1 1/2	4 1/2	2 1/8	6 1/4	7 1/4	3/8	5 1/16	1 1/4	SBM4145	3 3/4	3 1/4	3	7 5/8	6 5/8	7/16	1
4	2	W	75	600	Pin Size	Short Male Shroud	1 1/2	2	4 7/8	6 7/8	7 1/8	30" 10'	X8063-28	X8063-27	X8063-39 X8063-140	X8063-6 X8063-142	X8063-62	X8063-46	Term. Back	1 1/2	4 7/8	2 3/8	6 7/8	7 7/8	3/8	5	3	SBM4143	5 1/2	4 15/16	4 3/8	7 7/8	6 3/4	7/16	1
4	2	W	75	600	Pin Size	Full Male Shroud	1 13/16	1 7/8	4 13/16	7 1/2	5	30"	X8066-1	X8066-2																						
4	1	W	85	600	Pin Size	Full Male Shroud	2	2 1/4	5 1/2	8 1/2	6 3/16	45"	X8067-1	X8067-2																						