

Product designation	Two pedal, with safety lever on both pedals - both with cover
Product type designation	KRD002

General characteristics

Material

Housing

Aluminium-zinc alloy

Contact characteristics

Type of contact		2NO+2NC Snap action
Thermal current I _{th}	A	10
IEC/EN 60947-5-1 designation		A300 Q300
Rated insulation voltage U _i	V	440
Rated impulse withstand voltage U _{imp}	kV	4
Short-circuit protection with fuse	Class/A	10 gG fuse
IEC Conventional free air thermal current I _{th}	A	10
Resistance per pole (average value)	mΩ	<10

Mechanical features

Tightening torque (Max)

Contact terminals

Nm 1
lbin 0.74lbft

Cable connection Self-releasing screw terminal

Cable entry 1 x M20

Operations

Mechanical life cycles >10000000

Ambient conditions

Temperature

Operating temperature

min °C -25
max °C +70

Storage temperature

min °C -40
max °C +70

Resistance & Protection

IP degree

Terminals IP20
Body housing IP54

Pollution degree 3

Certifications and compliance

Compliance

EN 60447.
IEC/EN 60204-1
IEC/EN 60947-1
IEC/EN 60947-5-1

Certificates

EAC

ETIM classification

ETIM 8.0 EC001258 - Foot switch