Olympic

CABLE SELECTOR GUIDE

MULTI-CONDUCTOR UNSHIELDED CABLE

CONDUCTOR SIZE

NO. OF COND.	24 AWG P/N	PG. NO.	22 AWG P/N	PG. NO.	20 AWG P/N	PG. NO.	19 AWG P/N	PG. NO.	18 AWG P/N	PG. NO.	16 AWG P/N	PG. NO.	14 AWG P/N	PG. NO.	12 AWG P/N	PG. NO.
2	81012	CF	2002	31	2367	22	2368	22	2202TF	42	2302TF	42	2342	45	2362	45
			2002L	28	2781	31	2369	22	2202	32	2302	33	2342L	28	2362L	28
			2002T	29	2781T	29	2798	CF	2202L	28	2302L	28	2342T	29	2362T	29
			3130	72	3520	32			2202T	29	2302T	29	3118L	25	3135	72
			2365	22	3131	72			8200	76	2372	22	3134	72	8500	76
			2366	22	42002	36			2801	45	2373	22	3784-760A	27		
			2380	24	42002CF	34			3106L	25	3112L	25	8400	76		
			2601	44					3132	72	3133	72	41402	38		
									3752-725	29	3758-725	29	41402CF	35		
									3752-760	27	3758-760	27				
									41802	37	8300	76				
									41802CF	34	41602	37				
											41602CF	34				
3	81013	CF	2003	31	2103	31	2374	22	2203	32	2303	33	2343	33	2363	33
			2003L	28	3151	73	3026	CF	2203L	28	2375	22	3154	73	8502	76
			2003T	29	3521	32			2203T	29	3153	73	8402	76	41203	38
			3150	73	42003	36			3152	73	8302	76	41403	38	41203CF	35
					42003CF	34			8202	76	41603	37	41403CF	35		
									41803	37	41603CF	34				
									41803CF	34	9834	70				
4	81014	CF	2004	31	2104	31			2204	32	2304TF	42	2344	33	8503	76
			2004L	28	2104T	29			2204L	28	2304	33	2344T	29	41204	38
			2004T	29	3522	32			2204T	29	2304L	28	3119L	25	41204CF	35
			81004	CF	42004	36			3109L	25	2304T	29	3119T	27		
					42004CF	34			3754-725	29	3115L	25	8403	76		
									3754-760	27	3757-760	27	41404	38		
									8203	76	8303	76	41404CF	35		
									41804	37	41604	37				
									41804CF	34	41604CF	34				
5			2005	31	2105	31			2205	32	2305	33	2345	33	8504	76
			2005L	28	3523	32			2205L	28	8304	76	8404	46	41205	38
					42005	36			8204	76	41605	37	41405	38	41205CF	35
					42005CF	34			41805	37			41405CF	35		
									41805CF	34						
6	81016	CF	2006	31	2106	31			2206	32					8505	76
			2006L	28	3524	32			2206L	28						
			2006T	29					2206T	29						
			81006	CF					3756-725	29						
									3756-760	28						
7			2007	31	2107	31			2207	32	2307	33	2347	33	8506	76
			2007L	28	42007	36			2207L	28	8306	76	8406	76	41207	38
					42007CF	34			8206	76	41607	37	41407	38	41207CF	35
									41807	37	41607CF	34	41407CF	35		
									41807CF	34						
8	81018	CF	2008	31	2108	31			2208	32	8307	76	41408	38	8507	76
			2008L	28	3526	32			2208L	28	41608	37				
			2008T	29	42008	36			2208T	29						
			81008	CF					3759-725	29						
									8207	76						
9			2009	31	2109	31			2209	32	2309	33	2349	33	8508	76
			2009L	28	42009	36			2209L	28	8308	76	8408	76		
									41809	37	41609	37	41409	38		
10			2010	31	3527	32			2210	32	8309	76	8409	76	8509	76
			2010L	28	42010	36			2210L	28	41610	37	41410	38		
			2010T	29					2210T	29						
									41810	37						
									8209	76						
12			2012	31	2112	31			2212	32	2312	33	2352	33	8510	76
			2012L	28	3528	32			2212L	28	8310	76	8410	76		
			2012T	29	42012	36			2212T	29	41612	37	41412	38		
					42012CF	34			8210	76	41612CF	34	41412CF	35		
									41812	37						
									41812CF	34						
15			2015	31	2115	31			2215	32	2315	33	2355	33	8513	76
					3529	32			8213	76	41615	37	8413	76		
									41815	37						
19									2219	32	2319	33	8421	76	8521	76
									8221	76	8321	76				
20			2020	31	3530	32					8340	76	8440	76	8540	76
25			2025	31	42025	36			2225	32	2325	33	8445	76	8545	76
					42025CF	34			8245	76	8345	76	41425	38		
									41825	37	41625	37	41425CF	35		
									41825CF	34	41625CF	34				
30			2030	31	42030	36			41830	37	8349	76	8449	76	8549	76
											41630	38				
37									8250	76	8350	76	8450	76	8550	76
40			2040	31	42040	36			41840	37	41640	38				
50			2050	31	42050CF	34			41850	37	41650	38				
									41850CF	34	41650CF	34				
60			2060	31	42061	36			41861	37	41661CF	34				
					42061CF	34			41061CF	34						

RoHS Compliant

173010_olympic_catalog_2017_v9.indd 3 6/26/17 10:31 AM

Olympic

CABLE SELECTOR GUIDE

MULTI-PAIR UNSHIELDED CABLE

CONDUCTOR SIZE

NO. OF PAIRS	24 AWG P/N	24 AWG PG. NO.	22 AWG P/N	22 AWG PG. NO.	20 AWG P/N	20 AWG PG. NO.	18 AWG P/N	18 AWG PG. NO.	16 AWG P/N	16 AWG PG. NO.	14 AWG P/N	14 AWG PG. NO.	12 AWG P/N	12 AWG PG. NO.
1			2002 2002L 2002T 2365 2366 2380 2601 3130	31 28 29 22 22 24 44 72	2367 2781 2781T 3131	22 31 29 72	2202 2202L 2202T 2370 2801 3106L 3132 3752-725 3752-760	45 28 29 22 45 25 72 29 27	2302 2302L 2302T 2372 2373 3112L 3133 3758-760	45 28 29 22 22 25 72 27	2342 2342L 2342T 3118L 3134 3784-760A	33 28 29 25 72 27	2362 2362L 2362T 3122L 3122T 3135	33 28 29 25 27 72
2	3077	89	2602 2702	44 44			2802	45						
3	3079	89	2603 2703	44 44	2783	45	2803	45						
4	3078 3604 M5U	89 91	2604 2704	44 44			2804	45						
6	3080	89	2606 2706 6973	44 44 89	2786	45	2806	45						
9			2609 2709	44 44	2789	45	2809	45						
11			2611	44										
12	3081	89	2712 6974	44 89			2812	45						
13			2613	44										
15			2615 2715	44 44	2795	45	2815	45						
19			2619 2719	44 44			2819	45						
23			2623 2723	44 44										
25	3056 3083 3625 M5E	CF 89 91	6976	89										
27			2627 2727	44 44										
50	3085	89	2627 2727 6977	44 44 89										
75	3086	89												
100	3087	89	6978	89										

RoHS Compliant

173010_olympic_catalog_2017_v9.indd 4 6/26/17 10:31 AM

MULTI-CONDUCTOR CABLE

JACKETED/UNSHIELDED

UL CM/CL2, CE COMPLIANT

UNSHIELDED AUDIO CABLE SUNLIGHT RESISTANT



OLYMPIC NO.	UL STYLE NUMBER	NO. COND.	CONDUCTOR SIZE	CONDUCTOR STRAND	NOM. WALL THICK.	NOM. JACKET THICK.	NOM. O.D.	COLOR CODE	SUGG. WORK. VOLTAGE
2002		2	22	7/30	.010”	.032”	.164”		300
† **2003**		3	22	7/30	.010”	.032”	.169”		300
2004		4	22	7/30	.010”	.035”	.195”		300
2005		5	22	7/30	.010”	.032”	.199”		300
2006		6	22	7/30	.010”	.032”	.209”		300
2007		7	22	7/30	.010”	.032”	.214”		300
2008	**2464** (300v)	8	22	7/30	.010”	.032”	.224”	See Color Code Chart #8	300
† **2009**		9	22	7/30	.010”	.032”	.249”		300
2010		10	22	7/30	.010”	.032”	.259”		300
2012		12	22	7/30	.010”	.032”	.279”		300
2015		15	22	7/30	.010”	.032”	.304”		300
2020		20	22	7/30	.010”	.032”	.324”		300
2025		25	22	7/30	.010”	.032”	.364”		300
2030		30	22	7/30	.010”	.032”	.379”		300
2040		40	22	7/30	.010”	.032”	.439”		300
2050		50	22	7/30	.010”	.032”	.500”		300
† **2060**		60	22	7/30	.010”	.032”	.530”		
2781	**2464** (300V)	2	20	7/28	.013”	.025”	.180”	Black Red	300
† **2103**	**2509** (300V)	3	20	7/28	.016”	.020”	.190”	Chart 1	300
† **2104**	**2464** (300V)	4	20	7/28	.013”	.032”	.217”	Chart 1	300
† **2105**	**2464** (300V)	5	20	7/28	.013”	.032”	.239”	Chart 1	300
2106	**2509** (300V)	6	20	7/28	.016”	.025”	.255”	Chart 8	300
† **2107**	**2464** (300V)	7	20	7/28	.013”	.032”	.260”	Chart 1	300
† **2108**	**2509** (300V)	8	20	7/28	.016”	.020”	.270”	Chart 8	300
2109		9	20	7/28	.013”	.035”	.317”	Chart 1	300
† **2110**	**2464** (300v)	10	20	7/28	.016”	.032”	.350”	Chart 8	300
2112		12	20	7/28	.013”	.035”	.338”	Chart 1	300
2115		15	20	7/28	.013”	.040”	.389”	Chart 2	300

DESCRIPTION:
Stranded tinned copper, color coded PVC insulation, conductors twisted, gray PVC jacket overall.

APPLICATIONS:
Unbalanced intercom systems.
Low voltage relay control cable.
Electronic computer cable.
Interconnecting cables.
PA systems.
Remote control circuits.
Telephones & telemetering connecting cable.

TEMPERATURE RATING:
-20°C TO +105°C

† Not CE Compliant, 80˚C

RoHS Compliant

Passes the VW-1 vertical flame test

173010_olympic_catalog_2017_v9.indd 31 6/26/17 10:31 AM