DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Rolled Steel Jet Pump - J type Three-Phase	Product code :	14804535
		Catalog # :	00156ET3EJP56J-S

Frame	: 56J	Locked rotor time	: 30s (cold) 17s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 3.74/1.87 A	Protection degree	: IP55
L. R. Amperes	: 34.0/17.0 A	Cooling method	: IC411 - TEFC
LRC	: 9.1x(Code L)	Mounting	: F-1
No load current	: 1.72/0.859 A	Rotation[1]	: CCW
Rated speed	: 3520 rpm	Noise level[2]	: 68.0 dB(A)
Slip	: 2.22 %	Starting method	: Direct On Line
Rated torque	: 2.24 ft.lb	Approx. weight[3]	: 33.1 lb
Locked rotor torque	: 229 %		
Breakdown torque	: 300 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1023 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	78.4	80.0	82.5	84.0
Power Factor	0.44	0.71	0.82	0.88

Foundation loads	
Max. traction	: 66 lb
Max. compression	: 99 lb

		Drive end	Non drive end
Bearing type	:	6203 2RS	6202 2RS
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes
USABLE @208V 4.13A SF 1.00 SFA 4.13A

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	01/09/2020		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice