DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line	: W40 High Efficiency Three-Phase	Product code :	14282977
		Catalog # :	30036OP3HFP445TS-W40

Frame	: 444/5TS	Locked rotor time	: 32s (cold) 18s (hot)
Output	: 300 HP (220 kW)	Temperature rise	: 80 K
Poles	: 2	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 575 V	Altitude	: 1000 m.a.s.l.
Rated current	: 262 A	Protection degree	: IP23
L. R. Amperes	: 1700 A	Cooling method	: IC01 - ODP
LRC	: 6.5x(Code G)	Mounting	: F-1
No load current	: 60.2 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 3560 rpm	Starting method	: Direct On Line
Slip	: 1.11 %	Approx. weight[3]	: 1449 lb
Rated torque	: 443 ft.lb		
Locked rotor torque	: 130 %		
Breakdown torque	: 200 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 28.1 sq.ft.lb		
Design	: B		

Output	25%	50%	75%	100%
Efficiency (%)	93.5	94.1	94.5	95.0
Power Factor	0.62	0.85	0.88	0.89

Foundation loads

Max. traction	: 1634 lb
Max. compression	: 3084 lb

		Drive end	Non drive end
Bearing type	:	6314 C3	6212 Z C3
Sealing	:	Without Bearing Seal	Without Bearing Seal
Lubrication interval	:	14418 h	20000 h
Lubricant amount	:	27 g	13 g
Lubricant type	:	Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	06/02/2025		1 / 1	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice